

2.5 Litre, 3.0 Litre V6 and 4.2 Litre V8 S-TYPE

Vehicle Maintenance Sheet

DATE	VEHICLE REG. NO.	SPEEDO	INVOICE JOB NO.
------	------------------	--------	-----------------

VIN RANGE

2002.5 MY – From M44998

Maintenance must be carried out at 16 000 km (10 000 miles) or 12-monthly intervals from date of delivery, whichever comes first.

The Service Check Lists may be revised periodically. Franchise holders will be notified of revisions by Service Policy Letters or Technical Bulletins.

	16 000 km 10 000 miles	32 000 km 20 000 miles	48 000 km 30 000 miles	64 000 km 40 000 miles	80 000 km 50 000 miles	96 000 km 60 000 miles
Renew engine oil and oil filter. Renew drain plug sealing washer (V8). Renew drain plug assembly (V6).	X	X	X	X	X	X
Visually check underbonnet/underbody for any fluid leaks.	X	X	X	X	X	X
Inspect brake pads for wear (brake disc condition on pad change).	X	X	X	X	X	X
Renew coolant.	Every 5 years or 240 000 km (150 000 miles)					
Renew brake fluid.	Every 2 years					
Renew air cleaner element (all applications).				X		
Renew fuel filter.						X
Renew spark plugs (V6 only).	112 000 km (70 000 miles)					
Renew spark plugs (V8 only).	160 000 km (100 000 miles)					
Renew spark plugs (leaded fuel markets only).	X		X		X	
Check accessory drive belt tension wear indicator(s) – replace belt(s) if necessary.	X	X	X	X	X	X
Renew accessory drive belt.	240 000 km (150 000 miles)					
Renew supercharger drive belt (Supercharged only).	160 000 km (100 000 miles)					
Check/top-up brake fluid level.	X	X	X	X	X	X
Check/top-up coolant level.	X	X	X	X	X	X
Check/top-up windshield washer reservoir.	X	X	X	X	X	X

	16 000 km 10 000 miles	32 000 km 20 000 miles	48 000 km 30 000 miles	64 000 km 40 000 miles	80 000 km 50 000 miles	96 000 km 60 000 miles
Check/top-up battery electrolyte level.	X	X	X	X	X	X
Check/top-up power steering fluid level.	X	X	X	X	X	X
Renew windshield wiper blade rubber.	X	X	X		X	X
Renew windshield wiper blades.				X		
Check tyre pressures, tread depth, general condition, signs of uneven wear and suitability (including spare tyre).	X	X	X	X	X	X

	Front	Rear	Spare
Right-hand	<input style="width: 40px; height: 20px;" type="text"/> mm	<input style="width: 40px; height: 20px;" type="text"/> mm	<input style="width: 40px; height: 20px;" type="text"/> mm
Left-hand	<input style="width: 40px; height: 20px;" type="text"/> mm	<input style="width: 40px; height: 20px;" type="text"/> mm	

Renew pollen filters (under normal operating conditions).		X		X		X
Carry out road test.	X	X	X	X	X	X



2.5 Litre, 3.0 Litre V6 and 4.2 Litre V8 S-TYPE
Vehicle Maintenance Sheet

COMMENTS

SIGNATURE _____